

MCS-MS400V



Real Air Cooling

The multi-duct vortex refrigeration system and finned evaporator can prevent frosting completely and improve temperature uniformity to a large extent.

Real Energy Saving

The refrigerator is equipped with "M + Energy Core" power management system and complete air cooling design, improving energy saving efficiency by more than 40%.

M Real Visibility

The electrical heating + LOW-E design with double considerations can achieve a better anti-condensation effect for the glass door.

Real Safety

Seven temperature probes can ensure high precision of temperature control with nearly no fluctuation and thus can improve safety.



and 232/485 data access port.

Security System

- ·The well-developed audible & visual alarm system with multiple audible & visual alarm functions: high temperature alarm, low temperature alarm, sensor failure alarm, door ajar alarm, power failure alarm;
- The turn-on delay and stopping interval protection function can ensure reliability in running:
- \cdot The door is equipped with a lock, preventing it from opening accidentally.



Refrigeration System

Equipped with a compressor supplied by an international famous brand, high-efficiency air-cooled condenser and finned evaporator, ensuring fast refrigeration.





Data Storage

- · Equipped with a USB export interface
- · When a U-disk is connected, temperature data can be stored continuously and automatically (data can be stored for more than 2 years);
- ·The printer is optional.




Human-oriented


- Equipped with high-quality shelves made from PVC-coated steel wire with tag cards and classification marks, which are easy to clean;
- · Equipped with invisible door handle, ensuring elegance of appearance;
- · Equipped with testing port, bringing convenience to users in testing temperature inside the cabinet.

Scope of Application

Suitable for storage of biological products, vaccines, drugs, reagents, etc. Suitable for use in pharmacies, pharmaceutical factories, hospitals, centers for disease prevention & control, clinics, etc.

Performance Data / Cooling Curve





External Dimensions





2~8°C Pharmacy Refrigerator Model Cabinet Type Upright Capacity(L) Internal Size(W*D*H)mm MCS-MS400V Upright 400 604*520*1400 External Size(W*D*H)mm 700*645*2016	
Cabinet Type Upright Capacity(L) 400 Internal Size(W*D*H)mm 604*520*1400	
Capacity(L) 400 Internal Size(W*D*H)mm 604*520*1400	
Internal Size(W*D*H)mm 604*520*1400	
Evternal Size(W*D*H)mm 700*C4E*201C	
External Size(W*D*H)mm 700*645*2016	
Package Size(W*D*H)mm 765*710*2074	
NW/GW(Kgs) 116/127	
Performance	
Temperature Range 2~8°C	
Ambient Temperature 16-32°C	
Cooling Performance 5°C	
Climate Class N	
Controller Microprocessor	
Display Digital display	
Refrigeration	
Compressor 1pc	
Cooling Method Air cooling	
Defrost Mode Automatic	
Refrigerant R290	
Insulation Thickness(mm) 50	
Construction	
External Material Powder coated material	
Inner Material Stainless steel	
Shelves 6(coated steel wired shelf)	
Door Lock with Key Yes	
Lighting LED	
Access Port 1pc. Ø 25 mm	
Casters 4 (2 casters with brake)	
· (2 sactors with braine)	
Data Logging/Interval/Recording Time USB/Record every 10 minute / 2 years	
. (2 datatio man pranto)	
Data Logging/Interval/Recording Time USB/Record every 10 minute / 2 years	
Data Logging/Interval/Recording Time USB/Record every 10 minute / 2 years Door with Heater Yes	cure
Data Logging/Interval/Recording Time USB/Record every 10 minute / 2 years Poor with Heater Yes Alarm	ure
Data Logging/Interval/Recording Time USB/Record every 10 minute / 2 years Yes Alarm Temperature Electrical Power failure , Low battery,	cure
Data Logging/Interval/Recording Time USB/Record every 10 minute / 2 years Yes Alarm Temperature Electrical High/Low temperature, High ambient temperature, Condenser high temperature, Power failure, Low battery,	ure
Data Logging/Interval/Recording Time USB/Record every 10 minute / 2 years Yes Alarm Temperature Electrical Power failure, Low battery, System Sensor failure, Door ajar, Built-in datalogger USB Failure, Remote alarm	ture
Data Logging/Interval/Recording Time USB/Record every 10 minute / 2 years Yes Alarm Temperature High/Low temperature, High ambient temperature, Condenser high temperature, Low battery, System Sensor failure, Door ajar, Built-in datalogger USB Failure, Remote alarm Electrical	ure
Data Logging/Interval/Recording Time USB/Record every 10 minute / 2 years Yes Alarm Temperature Electrical System System Electrical Power Supply(V/HZ) 110/60 USB/Record every 10 minute / 2 years Yes Yes Alarm High/Low temperature, High ambient temperature, Condenser high temperature, Low battery, Sensor failure, Door ajar, Built-in datalogger USB Failure, Remote alarm Electrical	cure
Data Logging/Interval/Recording Time USB/Record every 10 minute / 2 years Yes Alarm Temperature High/Low temperature, High ambient temperature, Condenser high temperature, Low battery, System Sensor failure, Door ajar, Built-in datalogger USB Failure, Remote alarm Electrical Power Supply(V/HZ) 110/60 Power(W) 500	ture
Data Logging/Interval/Recording Time USB/Record every 10 minute / 2 years Yes Alarm Temperature High/Low temperature, High ambient temperature, Condenser high temperate Electrical Power failure, Low battery, System Sensor failure, Door ajar, Built-in datalogger USB Failure, Remote alarm Electrical Power Supply(V/HZ) 110/60 Power(W) 500 Power Consumption(KWh/24h) 4.5	ture
Data Logging/Interval/Recording Time USB/Record every 10 minute / 2 years Yes Alarm Temperature Electrical System Sensor failure, Door ajar, Built-in datalogger USB Failure, Remote alarm Electrical Power Supply(V/HZ) Power (W) Power Consumption(KWh/24h) Rated Current(A) Alarm High/Low temperature, High ambient temperature, Condenser high temperate temperature, Low battery, Sensor failure, Door ajar, Built-in datalogger USB Failure, Remote alarm 110/60 4.5	ure

^{*}The model, parameters and performance specified in this brochure may be changed without prior notice because of product upgrading.
*There may be differences between the product images shown in this brochure and the actual products. When you are buying any product, please check the actual product.

